



Attestato n° / Statement no.:

C1104\DC\REA\19_2

Visti i rapporti di prova CSI n. 1104\DC\REA\19_5, 1104\DC\REA\19_6, 0109/DC/TOX/19_1 e
0109/DC/TOX/19_2
*Referring to the CSI test reports n. 1104\DC\REA\19_5, 1104\DC\REA\19_6, 0109/DC/TOX/19_1 and
0109/DC/TOX/19_2*

si dichiara che
this is to declare that

PANGUA FIRE-RAIL (TUTTO PIOPPO)

(Pannello in compensato di pioppo unito con colla MUF resina melamminica e con trattamento
ignifugante HYDROFLAM W16) spessore da 8 a 30 mm
*(Poplar plywood panel joined with MUF melamine resin glue and with HYDROFLAM W16 flame retardant
treatment) from 8 to 30 mm thick*

Fabbricato da:
Manufactured by

PANGUANETA SPA
VIA SOLAZZI, 19
46018 SABBIONETA (MN)

è conforme alla norma
is found to comply with the standard

EN 45545-2:2013+A1:2015 requisiti R10 per HL1, HL2 e HL3
per le prove T04, T10.03 e T11.02
EN 45545-2:2013+A1:2015 requirements R10 for HL1, HL2 and HL3
for the tests T04, T10.03 and T11.02

Data di rilascio/certificate issue date: 21/10/2019

Ing. P. Fumagalli

pagina 1 di 1